

165 mm

1 mm



FWB31GS

FWB encl., univers, IP44,500x300x161, QC

Product Datasheet

rcł		

Fixing mode surface-mounting

Configuration

Module with terminals

Compatibility

Compatible with DIN rail mounting yes

Electric current

Rated current 125 A

Cover, door

Type of door closing	hinged pattern handle	
Number of keylock of the door	1	
Cover type	With Notch	
Door leave	single	
Door quantity	1	
Cover type	Door	
Transparent cover or door	yes	

Materials

Colour	white
RAL colour	RAL 9010 - Pure white
Material	Steel
Type of surface treatment	powder-coated

Dimensions

Internal depth	156 mm
Height of installed product	500 mm
Installation height	500 mm
Width of installed product	300 mm
Width in division units	12

Installation, mounting

Thickness of sidewall material

Depth of installed product

Suitable for outdoor use no

Connection

Number of conduit inlets 4



Accessories included

Mounting plate included	no
With lock	no
Equipment	
Number of rows	3
Quantity of section in width	1
Number of keys	1
Quantity of rails	3
Can be accessorized	yes
Number of openings for flange plates	2
Extension possible	yes
Standards	
European directive WEEE	concerned
Safety	
IK protection code against mecanical impacts	IK07
Protection index IP	IP44
Protection class	isol.class II