Product Data Sheet FWB41GS

FWB encl., univers, IP44,650x300x161, QC





FWB41GS

Architecture	
Fixing mode	surface-mountin
Configuration	
Module	with terminal
Compatibility Compatible with DIN rail mounting	ує
Electric current	
Rated current	125
Cover, door	
Type of door closing	hinged pattern hand
Number of keylock of the door	
Cover type	With Note
Door leave	sing
Door quantity	
Cover type	Doc
Transparent cover or door	уе
Materials	
Colour	white
RAL colour	RAL 9010 - Pure whit
Material	01-
Matchai	Stee
Type of surface treatment	powder-coate
Type of surface treatment	powder-coate
Type of surface treatment Dimensions	powder-coate 165 mi
Type of surface treatment Dimensions Depth of installed product	powder-coate 165 mi 156 mi
Type of surface treatment Dimensions Depth of installed product Internal depth Height of installed product	powder-coate 165 mi 156 mi 650 mi
Type of surface treatment Dimensions Depth of installed product Internal depth	powder-coate 165 mi 156 mi 650 mi 650 mi
Type of surface treatment Dimensions Depth of installed product Internal depth Height of installed product Installation height	powder-coate 165 mi 156 mi 650 mi 650 mi 300 mi
Type of surface treatment Dimensions Depth of installed product Internal depth Height of installed product Installation height Width of installed product	powder-coate 165 mi 156 mi 650 mi 650 mi 300 mi 1
Type of surface treatment Dimensions Depth of installed product Internal depth Height of installed product Installation height Width of installed product Width in division units Thickness of sidewall material	powder-coate 165 mi 156 mi 650 mi 650 mi 300 mi 1
Type of surface treatment Dimensions Depth of installed product Internal depth Height of installed product Installation height Width of installed product Width in division units	powder-coate 165 mr 156 mr 650 mr 650 mr 300 mr 1 1 mr
Type of surface treatment Dimensions Depth of installed product Internal depth Height of installed product Installation height Width of installed product Width in division units Thickness of sidewall material Installation, mounting	

Accessories included

Mounting plate included	no
With lock	no

Equipment

Number of rows	4
Quantity of section in width	1
Number of keys	1
Quantity of rails	4
Can be accessorized	yes
Number of openings for flange plates	2
Extension possible	yes

Standards

European directive WEEE	concerned
-------------------------	-----------

Safety

IK protection code against mecanical impacts	IK07
Protection index IP	IP44
Protection class	isol.class II