

16



#### FWB44GS

Product Datasheet	
Architecture	
Fixing mode	surface-mounting
Configuration	
Module	with terminals
Compatibility	
Compatible with DIN rail mounting	yes
Electric current	
Rated current	125 A
Cover, door	
Type of door closing	hinged pattern handle
Number of keylock of the door	1
Cover type	With Notch
Door leave	double symmetric
Door quantity	2
Cover type	Door
Transparent cover or door	yes
Materials	
Colour	white
RAL colour	RAL 9010 - Pure white
Material	Steel
Type of surface treatment	powder-coated
Dimensions	
Depth of installed product	165 mm
Internal depth	156 mm

Depth of installed product	165 mm
Internal depth	156 mm
Height of installed product	650 mm
Installation height	650 mm
Width of installed product	1050 mm
Width in division units	12
Thickness of sidewall material	1 mm

### Installation, mounting

FWB encl., univers, IP44,650x1050x161, QC

Suitable for outdoor use	no
--------------------------	----

#### Connection

Number of conduit inlets	
--------------------------	--

#### Accessories included

Mounting plate included	no
With lock	no

# Equipment Number of rows

Number of rows	16
Quantity of section in width	4
Number of keys	1
Quantity of rails	16
Can be accessorized	yes
Number of openings for flange plates	8
Extension possible	yes

## Standards

European directive WEEE	concerned
-------------------------	-----------

### Safety

IK protection code against mecanical impacts	IK07
Protection index IP	IP44
Protection class	isol.class II