

165 mm

1 mm



FWB encl., univers, IP44,950x1050x161, QC

Product Datasheet

Δrc			
Δrc	nita	ודייב	ıro

Fixing mode	surface-mounting
-------------	------------------

Configuration

Module	with terminals
--------	----------------

Compatibility

Compatible with DIN rail mounting	yes

Electric current

Rated current	125 A
---------------	-------

Cover, door

hinged pattern handle	
1	
With Notch	
double symmetric	
2	
Door	
yes	

Materials

Colour	white
RAL colour	RAL 9010 - Pure white
Material	Steel
Type of surface treatment	powder-coated

Dimensions

Internal depth	156 mm
Height of installed product	950 mm
Installation height	950 mm
Width of installed product	1050 mm
Width in division units	12

Installation, mounting

Thickness of sidewall material

Depth of installed product

Suitable for outdoor use	no
--------------------------	----

Connection

Number of conduit inlets	16
--------------------------	----



Accessories included

Mounting plate included	no
With lock	no
Equipment	
Number of rows	24
Quantity of section in width	4
Number of keys	1
Quantity of rails	24
Can be accessorized	yes
Number of openings for flange plates	8
Extension possible	yes
Standards	
European directive WEEE	concerned
Safety	
IK protection code against mecanical impacts	IK07
Protection index IP	IP44
Protection class	isol.class II