



HA407

Load break switch visib.breaking 4P 160A

Product Datasheet

Architecture

Type of order	Short thumb-grip
Number of poles	4 P
Type of pole	4 P
Type of case	Fixed built-in

Functions

Reversing switch	no
------------------	----

Controls and indicators

Motor drive integrated	no
------------------------	----

Main electrical features

Rated operational voltage Ue	380 / 415 V
------------------------------	-------------

Voltage

Rated insulation voltage	800 V
Rated impulse withstand voltage	8000 V

Electric current

Rated operational current in AC21 category B	160 A
Acceptable current rating with AC22 category A	160 A
Cut off current	20 kA
Rated current	160 A
Short-circuit current with gl-gG fuses	50 kA
Rated short-time withstand current 1s	4 kA
Rated operational current in AC21 category A	160 A
Rated operational current in AC23 category A	160 A
Acceptable current rating with AC23 category B	160 A

Power

Active power under 380/415 V, 50 Hz	63 kW
Total power loss under IN	9,9 W
Power loss per pole at In	3,3 W
Contact rating with 400 V in AC1	105 kW

Cover, door

Interlockable	yes
---------------	-----

Dimensions

Width of installed product	142 mm
----------------------------	--------

Installation, mounting

Fixation type	DIN rail mounting or back plate mounting
---------------	--

Connection

Connection cross-sect. rigid cable	95mm ²
Type of connection	Terminal

Equipment

Width available for insulation connection	95 mm ²
Motor drive optional	no

Standards

Standard text	IEC 60947-3
European directive WEEE	concerned

Safety

Protection index IP	IP00
---------------------	------

Use conditions

Operating temperature	-20...70 °C
-----------------------	-------------