



ESC226

## Contactor 25A, 2NC, 230V

Product Datasheet

### Architecture

Type of order	Not applicable
---------------	----------------

### Main electrical features

Rated operational voltage Ue	230 V
Frequency	50 Hz

### Voltage

Rated insulation voltage	250 V
Command voltage AC	230 V
Rated impulse withstand voltage	4 kV

### Electric current

Rated current	25 A
Thermal rated current outside of housings	25 A
Acceptable current load with AC7 category A	25 A
Acceptable current load with AC7 category B	8,5 A

### Power

Inrush power absorbed	10,7 VA
Operating consumption	2,9 VA
Total power loss under IN	2,9 W
Power loss per contact	1,5 W
Power dissipation per coil	2,9 W
Contact rating with 230 V in AC7 category A	4,6 kW
Contact rating with 230 V in AC7 category B	880 W

### Tripping

Time of response when opening	15 ms
Time of response when closing	25 ms

### Endurance

Electric endurance in number of cycles	30000
Number of mechanical operations	100000

### Dimensions

Depth of installed product	60 mm
Height of installed product	83 mm
Width of installed product	17,85 mm

### Fluorescent bulbs control

Max. power with fluorescent parallel lamps	810 VA
Fluorescent lamps in duo circuit	1990 VA
Max. load fluorescent lamp	950 VA

## Incandescent bulbs control

Max. power with incandescent lamps	1900 W
------------------------------------	--------

## Installation, mounting

Tightening torque	1,2Nm
-------------------	-------

## Connection

Connection cross-sect. flexible conductor	1 / 6mm <sup>2</sup>
Connection cross-sect. rigid cable	1 / 10mm <sup>2</sup>
Type of contacts	2NC
Type of connection	with screw
Cable connect. cross section (flexible) for control	1 / 6 mm <sup>2</sup>
Connection cross-section of the control cable solid	1 / 10 mm <sup>2</sup>

## Equipment

Can be accessorized	yes
With slide for manual switch	no

## Use

Local operation/hand operation	no
--------------------------------	----

## Standards

European directive WEEE	concerned
-------------------------	-----------

## Safety

Protection index IP	IP2X
---------------------	------

## Use conditions

Operating temperature	-10...50 °C
Storage/transport temperature	-40...80 °C