



HI454

Change-over switch 4P 250A

Product Datasheet

Architecture

Type of order	Long thumb-grip
Number of poles	4 P
Type of pole	4 P
Type of case	Fixed built-in

Functions

Reversing switch	yes
------------------	-----

Controls and indicators

Motor drive integrated	no
------------------------	----

Main electrical features

Rated operational voltage Ue	380 / 400 / 500 / 690 V
Frequency	50/60 Hz

Voltage

Rated insulation voltage	800 V
Rated impulse withstand voltage	8000 V
Rated operational voltage in DC	260 / 400 / 500 V

Electric current

Rated operational current in AC21 category B	250 A
Acceptable current rating with AC22 category A	250 A
Rated current	250 A
Short-circuit current with gl-gG fuses	50 kA
Rated short-time withstand current 1s	8 kA
Thermal rated current outside of housings	250 A
Rated operational current in AC21 category A	250 A
Acceptable current rating with AC22 category B	250 A
Rated operational current in AC23 category A	250 A
Acceptable current rating with AC23 category B	250 A

Power

Nominal power under 440/500, 50Hz	160 kW
Nominal power under 660 V, 50 Hz	110 kW
Active power under 380/415 V, 50 Hz	132 kW
Total power loss under I _N	17,4 W
Power loss per pole at I _n	5,9 W
Contact rating with 400 V in AC1	164 kW

Endurance

Electrical durability at nominal load in AC21 in operating cycles	1000
Electrical durability at nominal load in AC22 in operating cycles	200
Number of mechanical operations	10000

Cover, door

Interlockable	yes
---------------	-----

Connection

Connection cross-sect. rigid cable	95 / 150mm ²
Type of connection	Terminal

Equipment

Motor drive optional	no
----------------------	----

Standards

Standard text	IEC 60947-3
European directive WEEE	concerned

Safety

Protection index IP	IP00
---------------------	------

Use conditions

Air humidity protection	yes according to IEC 68-2-30
-------------------------	------------------------------