



**Trunking 12x20, L=2,1m, pure white**

Product Datasheet

**Architecture**

Fixing mode bottom punched

**Functions**

Suitable for functional integrity according to DIN 4102-12 no

**Configuration**

Antibacterial treatment no

**Connectivity**

Trunking coupling without coupler

**Capacity**

Maximum number of cables (Ø 11 mm, 50% fill) 1

**Cover, door**

Lid shape premounted

**Materials**

Colour pure white

RAL colour RAL 9010 - Pure white

Material PVC

Material group plastic

Type of surface treatment untreated

Transparent no

**Dimensions**

Trunking height 13 mm

Length 2100 mm

Trunking width 24 mm

**Installation, mounting**

Base punching Without base punching

**Cable**

Number of wires 1,5 mm<sup>2</sup> - 40% filling degree 14

Internal/useful cross section 240 mm<sup>2</sup>

Number of wires 2,5 mm<sup>2</sup> - 40% filling degree 10

**Scope of delivery**

Delivery on roll no

ATA122019010



**Equipment**

Number of fix dividers	1
Compartment quantity	2
Cable retainers per meter	2
Cable fixing clips included	yes
With protective film	no

**Standards**

Approvals	EN50085-2-1
European directive RoHs	voluntary compliance

**Safety**

Protection index IP	IP40
Halogen free	no
Impact strength	IK07

**Use conditions**

Operating temperature	-5...65 °C
-----------------------	------------